

HYUNDAI

16 CH NVR



Model: HY-XP16H46

- 8MP(4K), 5MP, 3MP ,2MP(1080P),1.3MP(960P),1.0MP(720P) real time recording;
- Max 16ch playback synchronously
- Onboard 4 SATA ports , each supports 6 TB
- Built-in high-power switching power supply
- Alarm audio and talk-back supported
- ONVIF 2.6 supported and compatible with almost all third-party IP cameras
- Up to 8 Mega pixels IP camera recording
- PTZ control via USB Mouse
- VGA, HDMI® and CVBS output sync
- HDMI® and VGA resolution up to 4K
- Built-in P2P Cloud service, firewall penetration automatically
- Always online , no need configuration for remote view anymore
- Mass of network protocols NTP, SADP (Camera Auto Discovery) , Email, RTSP, UPNP
- Support iPhone, Android, Windows Mobile Phone, BlackBerry and Symbian APPs
- Internet Explorer, Chrome, Firefox, Safari and center monitoring client supported

Specification:

| | |
|---------------------------|---|
| Model | HY-XP16H46 |
| Recording Bandwidth | Max 320Mbps |
| Recording Resolution | 8MP (4K), 5MP, 3MP ,2MP(1080P),1.3MP(960P),1.0MP(720P) |
| Display Split | 1/4/6/8/9/10/13/14/16 |
| live/Playback performance | 4K: 4ch realtime 4MP: 8ch realtime 3MP: 10ch realtime 2MP: 16ch realtime |
| Output Interface | 1 HDMI (up to 4K), 1 VGA |
| Display Resolution | 1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 1680*1050, 1600*1200, 1900*1200, 2560*1440, 3840*2160 |
| Alarm Input/out | 16ch in / 1ch out |
| Ethernet | RJ-45 port (1000M) |
| Smart Phone | iOS, Android |
| Internal HDD | 4 SATA HDDs, each HDD up to 8TB |
| RS485 | yes |
| e-Sata | yes |
| Line In | yes |
| USB | 1x3.0 USB for backup/upgrade , 2x 2.0 USB for mouse |
| ONVIF | yes |
| POE | NO |
| Power Supply | DC12V |
| Dimension (W×D×H) | 378*325.8*66mm |