

- ✦ 1/3" CMOS sensor SC2135
- ✦ 2MP resolution 1920(H)×1080(V) output
- ✦ Day/Night (IR), AWB, 2D/3D-DNR, IR-CUT
- ✦ TF Card Slot , 64GB MAX
- ✦ Wired & Wireless Connection way
- ✦ 25fps , 15fps Frame rate



Model	RE-Mono 2		
Chipset	Chipset	T20	
Image sensor	sensor type	1/3 inch 2.0MPixel CMOS sensor SC2135	
	resolution	1920×1080 pixels	
	min lux	0.1lux@f1.2(color mode) ;0.01 Lux(black and white)	
	S/N Ratio	2DNR, 3DNR >60dB	
	CMOS Features	Support AWB, AGC,BLC, DWDR,	
Lens	lens type	CS lens	
	lens	3.6mm	
	View Angle	60°	
	Day/Night vision	Yes IR-CUT dual filter	
	Night vision distance	30 meters	
Connection	Protocol	HTTP,FTP,TCP/IP,UDP,SMTP,NTP, IGMP, RTP,RTSP,ARP DHCP,PPPoE,DDNS,UPnP	
	Wired	Yes	
	Wireless	WIFI (IEEE 802.11b/g/n)	
	Wireless connection	one key to connect via soundwave match, QR code, Wired LAN	
	P2P	Yes	
	Network interface	1CH 10/100 base T Ethernet , RJ45 interface	
Main Function	Image compression way	H.264,MJPEG	
	Resolution	Main Stream	1920 x1080,1280x960x1280x720,720x576,640 x 480(VGA)
		Extra Steam	640 x 480(VGA), 352x288, 320x240
	Video output	CBR, VBR, 32K-10M	
	Frame rate	25fps, 15fps	
	Code rate	Dual	
	multi-media	Yes	
	Motion detection	Yes	
	E-mail/FTP Alarm	Yes	
	Pre-record	Yes	
	SD/TF card storage	Yes	
	UPnP	Yes	
	DDNS	Yes	
	onvif	Yes	
Storage	TF card slot,Max 64GB		
Audio	One way audio	Sound collect	
	inner microphone	Yes	
	Audio compression format	G711, PCM	
General	Size (mm)	104(L) x64(W) x64(H) measured without bracket	
	N.W (g)	300 (g)	
	Work Humidity	20%~85%	
	Work Temperature	-30°C~60°C	
	Storage humidity	0%-90%	
Platform	Device	iphone、 android mobile、 windows PC,app name:netcam	
Computer	CPU	2.0GHz	
	Flash	256M	
	Video card	64M	
	Operation system	Windows,Android2.3+,iOS7.0+	
	Browser	IE,google,firefox,Safari	