

HYUNDAI

4in1 IR Dome Camera

5MP 4in1 IR Dome Camera

Model: HY-AHD5D20IR-F



Features:


- 4-in-1 HDTV/HDCVI /AHD / CVBS optional output
- UHD resolution 2560×1944P CMOS sensor
- Ultra low illumination 0.02Lux
- Up to 300M long distance and high speed real time monitoring
- OSD menu control up the coaxial cable (UTC)
- Low light and perfect night vision
- Day/Night (ICR), AWB, AGC, DNR
- Lightning protection
- Strong water-proof housing, IP66
- 12 pcs New IR Leds, IR distance 15-20meters
- 3.6 mm fixed lens



2MP



5MP



WDR : OFF





WDR : ON



Specification:

Model	HY-AHD5D20IR-F
Camera	
Image Sensor	1/2.5" 5 Megapixels CMOS
Chipset	JX-K03+FH8538M
Effective Pixels	2704(H) × 1950 (V)
Video Resolution	AHD/TVI 20 fps@2560 × 1944P, CVI 30 fps@2560 × 1440P, adjustable
Electronic Shutter	AUTO, 1/25 - 1/50,000s
Min. Illumination	0.02Lux@F1.2(AGC ON), 0Lux IR on
Video System	PAL/NTSC
Video Output	1 channel, HDCVI / HDTVI/AHD/CVBS , adjustable
Video Switch	DIP switch
Day/Night	Auto/Color/(B/W)/EXT
White Balance	ATW/Manual
DNR	2D NR
OSD Menu	Multiple languages OSD menu control up the coaxial cable (UTC)
IR Led	
IR Led	12 pcs 850nm SMD IR Leds
IR Distance	15-20 M
Lens	
Focal length	3.6 mm fixed lens
General	
Power Supply	12 VDC ± 10%
Power Consumption	< 5 W
Operating Temp.	-20°C-(+60)°C, 10%-90%RH

Deminsion:



Full High Definition (5MP)



On-Screen Display



Low Light Illumination



Up The Coax



Weatherproof



Smart IR