



Specification :

Model Number		VU - 3016NX
Operating System		Embedded LINUX operating system
Image Code Control		Image code quality adjustable, variable bitstream optional
Dual Stream		Each channel can set main stream and sub stream
Video Standard		H.264
Monitoring Image Quality		5MP(2592x1944)/3MP(2048x1536)/1080P(1920x1080)/960P(1280*960)
Image Motion Detection		Each screen can set mutiple detection areas and set 6-level sensitivity (IPC Support)
Recording Playback Quality		1/4/9/16ch synchronous playback
Region Cover		Every channel can set 4 cover regions (IPC Support)
Recording Mode		Support manual, auto, motion detecion, alarm trigger record mode
Backup Way		Support U disk, USB mobile HDD, network storage and backup
Operation Way		Mouse
Local Login		User name and password
Recording Storage		Local HDD, network
External Ports	Video Input	① 36x(1280*960)+sub[960*576]+4Ref.+9Play 36ch 1.3MP IP Camera
		② 25x(1920*1080)+sub[960*576]+4Ref.+4Play 25ch 2.0MP IP Camera
		③ 16x(2048*1536)+sub[960*576]+4Ref.+4Play 16ch 3.0MP IP Camera
		④ 16x(2592*1944)+sub[960*576]+4Ref.+1Play 16ch 5.0MP IP Camera
	Audio Input	36/25ch network audio input
	Video Output	1ch VGA+1ch HDMI
	Network Port	1 RJ45, 10M/100M/1000M self-adaptive LAN port
	USB Port	1xUSB 3.0 ports, 2xUSB 2.0 ports
	Alarm Input	4ch
	Alarm Output	1ch
HDD	HDD Port	4xSATA + 1xE-SATA HDD Port
	MAX Capacity	Each port supports MAX 6TB HDD
Mobile Surveillance		Support(iPhone, Windows Mobile, Android) smart phone
Power Supply		ATX110-220V 250W 50-60Hz
Power Consumption		≤25W(without HDD)
Working Temperature		-10°C~+55°C
Working Humidity		10%-90%
Dimension		Equipment: 440mmx356mmx68.5mm, Packing: 460mmx135mmx560 mm
Weight(without HDD)		N.W.: 5.7k; With Package: 6.9Kg
Outside Carton		4 pcs/carton. 480mmx560mmx575mm; Weight: 30Kg
Installation Way		Desktop Installation