



Specification :

Model Number		VU - 3009N
Operating System	Embedded LINUX operating system	
Image Code Control	Image code quality adjustable, variable bitstream optional	
Dual Stream	Each channel can set main stream and sub stream	
Video Standard	H.264	
Monitoring Image Quality	5MP(2592x1944)/3MP(2048x1536)/1080P(1920x1080)/960P(1280*960)	
Image Motion Detection	Each screen can set multiple detection areas and set 6-level sensitivity (IPC Support)	
Recording Playback Quality	Any 9ch 960P playback, 4ch 5MP/3MP/1080P playback simultaneously	
Region Cover	Every channel can set 4 cover regions (IPC Support)	
Recording Mode	Support manual, auto, motion detection, alarm trigger record mode	
Backup Way	Support U disk, USB mobile HDD, network storage and backup	
Operation Way	Mouse	
Local Login	User name and password	
Recording Storage	Local HDD, network	
External Ports	Video Input	① 9x(1920*1080)+sub[960*576]+4Ref.+4Play 9ch 2.0MP IP Camera
		② 9x(1280*960)+sub[720*576]+4Ref.+9Play 9ch 1.3MP IP Camera
		③ 9x(2048*1536)+sub[960*576]+4Ref.+4Play 9ch 3.0MP IP Camera
		④ 9x(2592*1944)+sub [960*576]+4Ref.+1Play 9ch 5.0MP IP Camera
	Audio Input	9 network audio input
	Audio Output	1ch RCA
	Video Output	1ch VGA+1ch HDMI
HDD	Network Port	1 RJ45, 10M/100M/1000M self-adaptive LAN port
	USB Port	2xUSB 2.0 ports
	HDD Port	2xSATA HDD Port
	MAX Capacity	Each port supports MAX 6TB HDD
Mobile Surveillance	Support(iPhone, Windows Mobile, Android) smart phone	
Power Supply	12V3A	
Power Consumption	≤20W(without HDD)	
Working Temperature	-10°C~+55°C	
Working Humidity	10%-90%	
Dimension	Equipment: 350mm×240mm×68mm, Packing: 409mm×365mm×129mm	
Weight(without HDD)	N.W.: 1.35Kg; With Package: 2.3Kg	
Outside Carton	5 pcs/carton. 675mm×425mm×385mm; Weight: 12.5Kg	
Installation Way	Desktop Installation	